



5/8" Coaxial Cable Connectors

Available
2007

ITEM NUMBER	DESCRIPTION
NM50V58	N-male, O-ring
NF50V58	N-female, O-ring
7/16M50V58	7/16 DIN male, O-ring
7/16F50V58	7/16 DIN female, O-ring

ELECTRICAL

• Nominal impedance, Ω	50
• Return loss @ 2.5 GHz, dB	-35
• 3rd order intermodulation product, dBc	-163
• Temperature range	-40°F to +140°F (-40°C to +60°C)
• Water immersion testing	IP67 & IP68
• Materials	
External parts	Passivated silver plated or electroless nickel plated brass
• Outer contact	Passivated silver plated brass
• Inner contact	Passivated silver plated Cu-Be
• Dielectric	TXP / PTFE
• O-rings	Silicone rubber

ACCESSORIES

For complete accessory, refer to Eupen Site Steel & Accessory Catalog.

DESCRIPTION	ITEM NUMBER
Hoisting Grips	
Lace-Up Hoisting Grip	HG-58
Pre-Laced Hoisting Grip	HG-58L
Hangers	
Butterfly Hangers, Kit of 10	BH-58-NH
Snap-In Hangers, Kit of 10	SH-U58
Coax Support Blocks	
Mini Coax Support Blks, Kit of 10	CB-58
Large Coax Support Blks, Kit of 10	CB-58L

DESCRIPTION	ITEM NUMBER
Angle Adapters, Stainless Steel	
Universal SST Angle Adaptor, Kit of 10	AA-U
SST Angle Adaptor, Kit of 10	AA-SL
Weatherproofing	
Standard Weatherproofing Kit	WK-U
Boots and Cushions	
4" Boot Assembly, 1 hole	BA-58-1A
4" Boot Assembly, 3 hole	BA-58-3A
Standard Port Cushion, 1 hole	SC-58-1
Standard Port Cushion, 2 hole	SC-58-2
Standard Port Cushion, 3 hole	SC-58-3
4" Boot Assembly, Cushion not included	BA-400
5" Boot Assembly, Cushion not included	BA-500